DPA

DPA Circulation Pump
For Hot Water



Application Limits

- ◎ Liquid temperature: +2°C ~ +90°C
- ◎ Maximum ambient temperature +40°C
- ◎ Maximum system pressure 10bar
- ◎ Protection level: IP44
- ◎ Mains connection: 220V/50Hz、220V/60Hz、127V/60Hz
- ◎ Insulation class: H
- ◎ Pumped liquid characteristics: clean, free from solids and mineral oils, non-toxic, chemically neutral, close to the characteristics of water
  Installation: the motor shaft must be kept in
- ◎ horizontal direction
  pH: 6.5 to 8.5

Advantages & Features

- ◎ Automatic mode and manual mode is available Low noise, no leakage
- ◎ Flow switch automatic control

Performance Data

Model	Speed	Input Power P_1(W)	Current(A)	Capacitor	Inlet Outlet (mm)	Max. head (m)	Whole lift (m)	Max. flow (l/min)	Inter Box		Outer Box			20" Loading Qty (pcs)
			220V 50Hz/60Hz	μF/450V 220V 50Hz/60Hz					G.W. (kg)	Dim. (L×W×H)	PCS/ CTN	Dim (L×W×H)	G.W. (kg)	
DPA15-9-160	–	120	0.5	3	20	9	0~9	27	2.8	180x120x135	8	380x260x290	23	5880